



Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Rated power in W	800 W
Rated power in VA	1000 VA
Nb of power socket outlets	3 IEC 60320 C13
Output voltage	230 V
Output voltage	220 V 240 V
Input voltage	220 V 240 V
Input voltage	230 V
Plug standard	IEC 60320 C14
Cable length	1.50 M
Number of cables	1

General

Max runtime	4 Min
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Provided equipment	Basic UPS signalling RS-232 cable CD with software User manual USB cable

Physical

Mounting mode	Not rack-mountable
Height	22.3 Cm
Width	14.5 Cm
Depth	28.8 Cm
Net weight	9.3 Kg
Colour	Black

Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE EAC TISI
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Acoustic level	50 dBA
Heat dissipation	372 Btu/H
Operating altitude	0...3000 m
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15000 M
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	Non-condensing 0...95 %

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	24 V
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	4 H
Battery life	3...5 Year(S)
Battery charger power	30 W rated

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	10.6 Kg
Package 1 Height	33 Cm
Package 1 width	23.5 Cm
Package 1 Length	36.5 Cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 ans (défaut de fabrication)
----------	-------------------------------

Product Life Status :	Commercialised
-----------------------	----------------